

SAC SECURIZAT PENTRU TRANSPORT ATM



APLICAȚII

- Transportul casetelor ATM

MATERIAL

- Bumbac ignifug
- Densitate: 400-470 g/m²
- Fundul sacului placat cu aluminiu dur 5mm
- 4 roti rotative cu rulment
- Coltare metalice protectie lovire
- 2 randuri de ocheti metalici 10 mm pentru sigilare
- Manere transport
- Burete sau folie PP, grosime 3-5mm aplicata in interiorul sacului pentru protectia casetelor lateral si fund sac
- Se pot confectiona si alte dimensiuni sau fara roti, la cerere

CARACTERISTICI

- Dimensiuni: L 100 x l 75 cm
- Sac transport casete terminale bancare prevazut cu burete pentru protectie si roti pentru o manevrare usoara si fara efort fizic

MARCAJE

La cerere: videoflex/laser:

- Logo
- Text

CULORI

- Negru
- Maro
- Bleumarin

AMBALARE

- Livrare/buc
- Greutate: 4,5 Kg



SECURE TRANSPORT BAG FOR ATM



APPLICATIONS

- Transportul casetelor ATM

MATERIAL

- Flame retardant cotton
- Density: 400-470 g/m²
- The bottom of the bag is plated with hard aluminum 5mm
- 4 rotating wheels with bearing
- Metal collars for impact protection
- 2 rows of 10 mm metal eyelets for sealing
- Transport handles
- Sponge or PP foil, 3-5mm thick applied inside the bag to protect the sides and bottom boxes
- Other sizes or without wheels option can be made on request

CHARACTERISTICS

- Dimensions: L 100 x l 75 cm
- Transport bag for bank terminal boxes with sponge for protection and wheels for easy and effortless handling

MARKINGS

Upon request: videoflex/laser:

- Logo
- Text

COLORS

- Black
- Brown
- Navy blue

PACKAGING

- Shipment/piece
- Weight: 4,5 Kg

